

Product Overview



IceBreaker® selection table

Technical Data

		AIRCOAT	AIRCOAT	AIRCOAT	AIRCOAT	AIRCOAT
		Wildcat 10-70	Puma 15-70	Puma 15-150	Wildcat 18-40	Leopard 18-300
Piston pump						
Pump ratio		10 : 1	15 : 1	15 : 1	18 : 1	18 : 1
Max. working pressure	[bar]	80	120	120	145	140
Double-stroke volume	[cm ³ /DS]	70	70	150	40	300
Max. delivery rate	[L/min]	4.2	4.2	9.0	2.4	18.0
Air pressure (min/max)	[bar]	1.5/8.0	1.5/8.0	1.5/8.0	1.5/8.0	1.5/7.7
Air supply	internal thread	G 1/2"	G 1/2"	G 1/2"	G 1/2"	G 1/2"
Material inlet	external thread	M 36 x 2	M 36 x 2	M 36 x 2	M 36 x 2	M 36 x 2
Material outlet	external thread	3/8" NPS	3/8" NPS	3/8" NPS	3/8" NPS	3/4" NPS
Packing material	Standard Alternative	PE/TG PE/T	PE/TG PE/T	PE/TG PE/T	PE/TG PE/T	PE/TG PE/T
Max. number of guns	Nozzle 0,009"	> 6	> 6	–	5	–
Max. number of guns	Nozzle 0,013"	4	4	9	2	> 6
Max. number of guns	Nozzle 0,017"	2	2	5	–	> 6



Puma 28-40



Leopard 35-70



Tiger 72-300

AIRCOAT	AIRLESS	AIRCOAT	AIRLESS	AIRCOAT	AIRLESS	AIRCOAT	AIRLESS	AIRLESS	AIRLESS	AIRLESS	
Puma 28-40	Leopard 35-70	Leopard 35-150	Jaguar 38-300	Leopard 48-110	Jaguar 75-150	Tiger 72-300					
28 : 1	35 : 1	35 : 1	38 : 1	48 : 1	75 : 1	72 : 1					
225	250	270	270	370	530	530					
40	70	150	300	110	150	300					
2.4	4.2	9.0	18.0	6.6	9.0	12.0					
1.5/8.0	1.5/7.1	1.5/7.7	1.5/7.1	1.5/7.7	1.5/7.1	1.5/7.4					
G 1/2"	G 1/2"	G 1/2"	G 1"	G 1/2"	G 1"	G 1"					
M 36 x 2	M 36 x 2	M 36 x 2	M 36 x 2	M 36 x 2	M 36 x 2	M 36 x 2					
3/8" NPS	3/8" NPS	3/8" NPS	3/4" NPS	3/8" NPS	3/8" NPS	3/4" NPS					
PE/TG PE/T	PE/TG PE/T	PE/TG PE/T	PE/TG PE/T	PE/TG PE/T PE/L	PE/TG PE/T PE/L	PE/TG PE/T PE/L					
5	> 6	-	-	-	-	-					
2	4	> 6	> 6	6	> 6	> 6					
-	2	5	> 6	3	5	6					